New line: STAR EVOLUTION

New way of thinking a packaging machine. Clean, essential, high quality & flexibility. What the packaging had still not seen. For a easier way to work and always higher performances.

>> general features

STAR EVOLUTION.

3 belts side sealing machine.

For high flexibility.

Product's height up 300 mm. Film saving.

Energy saving for a tight nice bag. Canter level structure that allows easy cleaning and accessibility of the machine. Available in stainless steel version.

Possibily to create a customised machine adding desiderd options from optionals list.

>> specific features

STAR EVOLUTION design available in Combo version (with Tunnel combined or with separate shrink tunnel) capable to work with different sealing systems with all kinds of film. POF, PE, BOPP, OPP, CAST. Center Folded, and Flat film also in the same machine (patented system).

Film can be neutral or pre-printed.

Available in box motion & intermittent motion version depending on the speed required.


>> details



Touch screen intuitive and for easy change of format. Touch screen can rotate in 3 positions. Operator can operate and access the machine from the FRONT/BACK & SIDE. Machine is left/right.



Extractable film dispenser unit. For easy film
Easy connectors for each part to reduce optionally work with center folded and Flat manual working.




threading & quick change. Machine can working and stop timing. Operator's




Movable center conveyor belt. To let pro-Electric cabinet on view. Perfect for opeducts run always in the middle. No need to rator's maintenance and on high position. move the tunnel or the in feed conveyor belt.





Standard with product's passage: 300 mm. Higher flexibility. Mechanic on view.



seal bar. sliding doors.




Wider versions available up to 800 mm. Canter level structure for accessibility, cleaning, maintanance. User friendly. Combo



High quality components, ISO certificated.


leader in the manufacturing packaging equipment >>STAR EVO



evel 3 belts side sealing evolutions >> technical features

	- 3				
MOD.	500	500 COMBO	600	600 COMBO	800
Sealing dimensions	500 mm	500 mm	600 mm	600 mm	800 mm
Max product width	400 mm	400 mm	500 mm	500 mm	700 mm
Max product length	unlimited	unlimited	unlimited	unlimited	unlimited
Max product height	300 mm				
Film width (center Folded sizes)	650 mm	650 mm	750 mm	750 mm	950 mm
Reel diameter	350 mm				
Working height	900+/- 50	900+/- 50	900+/- 50	900+/- 50	900+/- 50
Machine weight	800 Kg	800 Kg	800 Kg	800 Kg	900 Kg
Speed - intermittent	65 p/min	65 p/min	65 p/min	65 p/min	40 p/min
Speed - box motion	100 p/min		100 p/min		70 p/min
Dimensions	2330x1250x1950 +/- 50(H)	3450x1250x1950 +/- 50(H)	2330x1350x1950 +/- 50(H)	3450x1350x1950 +/- 50(H)	3330x1850x1950 +/- 50(H)

STAR EVO line: possibility to have a separate or combined Tunnel. Intermittent or box motion versions available. Box motion versions only on separate versions not compact. Combo versions are only intermittent motion.



Standard: product's height up 300 mm.

Product's height up: 400 mm. Siemens touch screen. With 30 different programs.

Easy set up.

Accessible canter level structure, completely open: perfect for maintanance. Openable doors or sliding as an option.

Canter level sealing bar. High precision movement. Intermittent or Box motion

Movable central conveyor to have products running always in center. No need to move in feed conveyor or tunnel.